

### Standard Features

- Touchless IR (infrared) sensors minimize keypad use
- Program IR sensor to control operations including print, tare and other selectable functions
- Color VGA, 5.7 in display with icons for simple menu navigation
- Multiple application modes designed for versatility
- AutoCal™ calibration
- Robust IP 54 die-cast metal bottom housing with stainless steel pan
- Integral weigh below hook
- ENERGY STAR qualified adapter

### Specifications

#### Weighing Units:

Gram, Kilogram, Ounce, Pound, Carat, Pennyweight, Grain (See technical manual for complete listing)

#### Operating Modes:

Weighing, counting, Animal/Dynamic Weighing, Checkweighing, Percent Weighing, Filling, Parts Counting, Totalization, Formulation, Differential Weighing, Density Determination, Peak Hold, Ingredient Costing, SQC

#### Power:

AC adapter input: 100 to 240 VAC 0.6A 50 /60 Hz

#### Stabilization Time:

1 seconds

#### Calibration:

AutoCal™ at 1.5 °C temperature change, 11 hours, and external calibration

#### Operating Temperature:

-10 °C to 60 °C (14 °F to 140 °F)

#### Est. Weight:

25 lb (12.5 kg)

#### Warranty:

Two-year limited

#### Return Policy:

OHAUS standard policy - restock fee may apply

| Model          | Capacity | Readability | Repeatability | Linearity | Pan Size                           | Dimensions                                      | Part #        | List Price |
|----------------|----------|-------------|---------------|-----------|------------------------------------|-------------------------------------------------|---------------|------------|
| <b>Ex12001</b> | 12,000 g | 0.1 g       | ±0.1 g        | ±0.2 g    | 14.84 × 12.24 in<br>(377 × 311 mm) | 14.84 × 4.72 × 17.44 in<br>(377 × 120 × 443 mm) | <b>157235</b> | Consult    |
| <b>Ex24001</b> | 24,000 g | 0.1 g       | ±0.1 g        | ±0.2 g    | 14.84 × 12.24 in<br>(377 × 311 mm) | 14.84 × 4.72 × 17.44 in<br>(377 × 120 × 443 mm) | <b>157236</b> | Consult    |
| <b>Ex35001</b> | 35,000 g | 0.1 g       | ±0.1 g        | ±0.2 g    | 14.84 × 12.24 in<br>(377 × 311 mm) | 14.84 × 4.72 × 17.44 in<br>(377 × 120 × 443 mm) | <b>157237</b> | Consult    |

### Options/Accessories

| Part #        | Model #  | Description                   | Price   |
|---------------|----------|-------------------------------|---------|
| <b>157238</b> | 30078082 | Tower mount display           | Consult |
| <b>77712</b>  | 80500524 | RS-232 cable, PC 25-pin to EX | Consult |
| <b>70406</b>  | 80500525 | RS-232 cable, PC 9-pin to EX  | Consult |
| <b>156234</b> | 46001724 | Multi-range AC adapter        | Consult |
| <b>156235</b> | 46001780 | International plug set        | Consult |

