

Standard Features

- External weight calibration
- Seven-segment (main)/ 16-segment (sub) display
- Selectable modes: Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal and Formulation
- Mono-metal tuning fork technology (MMTF) provides quick response and stability
- 30-step bar graph display
- AA dry-cell port, (150 hours continuous use with LCD backlight and communication signal ON)
- RS-232 interface for connecting to printer or PC
- Glass breeze break (TE-223, TE-322NC and TE-623 only)

Specifications

Weighing Units:

Milligram, Gram, Ounce, Pound, Carat, Pennyweight, Troy Ounce (see technical manual for complete listing)

Operating Modes:

Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal, Formulation

Power:

100 to 240 V AC adapter, AA dry cell (batteries not included)

Operating Temperature:

41 °F to 95 °F (5 °C to 35 °C)

Est. Weight:

TE-223 / 322NC: 6.5 lb (3 kg)
 TE-623 / 3202 / 6202 / 15001 / 1501NC / 8200NC:
 6.0 lb (2.7 kg)

Warranty:

Five-year limited

Return Policy:

Rice Lake standard policy

Approvals:

NTEP Certified CC 17-104
 Measurement Canada AM-6169



Model	Capacity	Resolution	NTEP Resolution	Pan Size	Weighing Chamber	Dimensions	Part #	List Price
NTEP Certified Only								
TE-223	220 g	0.001 g	0.01 g	4.6 in (118 mm)	226 mm H x 150 mm W x 150 mm D	10.6 x 8.1 x 11.8 in (270 x 208 x 301 mm)	187600	Consult
TE-623	620 g	0.001 g	0.01 g	4.6 in (118 mm)	N/A	10.6 x 8.1 x 11.8 in (270 x 208 x 301 mm)	186030	Consult
TE-3202	3,200 g	0.01 g	0.1 g	6.3 x 7.1 in (160 x 180 mm)	N/A	10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)	186035	Consult
TE-6202	6,200 g	0.01 g	0.1 g	6.3 x 7.1 in (160 x 180 mm)	N/A	10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)	186036	Consult
TE-15001	15,000 g	0.1 g	1.0 g	6.3 x 7.1 in (160 x 180 mm)	N/A	10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)	186037	Consult
NTEP Certified and Measurement Canada Approved								
TE-322NC	320 g	0.01 g	0.01 g	4.6 in (118 mm)	226 mm H x 150 mm W x 150 mm D	10.6 x 8.1 x 11.8 in (270 x 208 x 301 mm)	204688	Consult
TE-1501NC	1,500 g	0.1 g	0.1 g	6.3 x 7.1 in (160 x 180 mm)	N/A	10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)	204689	Consult
TE-8200NC	8,200 g	1 g	1 g	6.3 x 7.1 in (160 x 180 mm)	N/A	10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)	204690	Consult

Options/Accessories

Part#	Description	Price
186074	Power supply 100-240 VAC, 50-60 Hz	Consult
186075	In-use dust cover 620 g models and lower	Consult
186076	In-use dust cover 3,200 g models and higher	Consult
186077	Specific Density Measurement Kit	Consult
186079	Ethernet TCP/IP option card	Consult

