

SURVIVOR® PT-M

Levertronic, Concrete Deck



Due to the variety of configurations, please consult the factory to discuss application requirements and for complete specifications and price quotations.

Approvals



Package includes: Steel weighbridge; lever system; inboard transverse lever (for electronic conversion) is furnished unless outboard lever is specified at time of order; standard paint system is a high-performance epoxy base coat.

Package does not include:

Foundation rebar; corrugated sheeting; pit angle coping; deck rebar; bumper plates; foundation bolts; assembly bolts; home run cable; concrete; indicator; printer; freight charges including material handling, shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.

Standard Features

- In-pit foundation
- Ideal for limited access locations
- Structural steel pipe lever system
- NTEP Certified 05-018
- Standard levers: 32.5 ton sectional rating
- Capacities to 400,000 lb
- Standard widths from 10 to 14 ft
- Standard profile 44.5 in

Options

- Load cell stand
- Steel deck
- Pit angle coping
- Deck rebar
- Deck channel
- Bumper plates
- Foundation bolts
- Manhole frames and covers
- Conversion s-beam load cell(s)
- Load cell mounting hardware
- Indicator
- Printer
- Other peripheral equipment

Specifications

Full Scale Capacity:

Standard 60,000 to 200,000 lb
Custom up to 400,000 lb

Concentrated Load Capacity (CLC):

Standard 50,000 to 70,000 lb
Custom up to 100,000 lb

Warranty:

Pivots, bearings, suspension and mounting parts of the corner assemblies: One-year
Weighbridge: Two-year

Approvals:

NTEP Certified 05-018 per H-44, Class III L
Measurement Canada AM-5598