

SURVIVOR® OTR-LP

Low-profile, Steel Deck



Due to the variety of configurations, please consult the factory to discuss application requirements and for complete specifications and price quotations.

Approvals



Package includes: Assembled weighbridge modules and weighbridge fasteners; load cells with conduit fitting; load cell mounts with leveling bolts and anchor bolts; copper transient bypass cables at each load cell; metal conduit on weighbridge for load cell cable runs; poly-coated flexible steel conduit from load cell to metal conduit; conduit fittings from poly-coated flexible steel conduit to metal conduit; FRP junction box(es); homerun cable to indicator (60 ft long); print packages including foundation drawing (pier, floating slab or pit) and installation manual.

Package does not include: Approach coping; foundation alignment posts; rebar and mesh for foundation; indicator; printer; freight charges including material handling; shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.

Standard Features

- Built to fit existing truck scale foundations
- Longitudinal I-beam construction
- Integrated load cell pockets
- Boltless, top access to load cells and junction box
- Self-seating, P-bracket connection between modules
- G-force mount assemblies return the scale to center without check rods or bumper bolts
- Cables completely encased in rodent-proof conduit
- Thorough finishing process includes cleaning of steel before and after welding, followed by either high solids urethane liquid paint or durable powder paint

Options

- 10 lb division for truck or livestock
- 20 lb division
- Schedule 40 guiderails
- Schedule 80 guiderails
- Manhole
- Slotted manhole
- Dolly down plate
- End cleanout
- Stainless steel load cells
- Tapered links and radius blocks
- Pre-suspended load cells and mounts
- Stainless steel suspension hardware
- Galvanized weighbridge and suspension hardware
- Corrosion-resistant coating
- 3/8-inch runners
- Roll-off
- Side deflector plates
- Catwalk
- Landing with stairs
- iQUBE²® digital diagnostic junction box bundles

Specifications

Load Cells:

Rice Lake RL75058-LP alloy steel,
Double -ended beam
75,000 lb capacity

Mount Assemblies:

G-force self-checking mounting system

Junction Box:

JB8SPT Tuffseal® polycarbonate NEMA Type 4X enclosure with overlapping solid cover, stainless steel screws

Platform Size:

10 to 160 ft length
10 ft and 11 ft width

Scale Profile:

11 to 16 in

Deck Thickness:

Steel: 8 in
Concrete: 10 in

Full Scale Capacity:

Up to 200,000 lb

Concentrated Load Capacity (CLC):

90,000 lb

Dual Tandem Axle (DTA):

90,000 lb

Warranty:

Weighbridge: 5-year or 12-year limited
Parts: 5-year or 12-year limited,
including lightning protection

Approvals:

NTEP CC 02-003, Class III
Measurement Canada AM-5413