

SURVIVOR® ATV-M

Self-Contained Levertronic, Steel Deck



Due to the variety of configurations, please consult the factory to discuss application requirements and for complete specifications and price quotations.

Approvals



Package includes: Factory-assembled scale module(s) including weighbridge, deck, lever system installed in scale frame; inboard transverse lever (for electronic conversion) is supplied standard unless outboard transverse lever is specified at time of order; manhole access provided through scale deck; standard paint system is a high-performance epoxy primer on all steel with a top coat of alkyd enamel applied to the exterior surface steel.

Package does not include:

Foundation steel; approach coping angle; home run cable; concrete; indicator; printer; freight charges including material handling, shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.

Standard Features

- Above-ground or in-pit foundation
- Factory-assembled, self-contained modules
- Individual module lengths from 10 ft to 40 ft
- Multiple modules create desired scale length
- Standard levers: 32.5 ton sectional rating
- Standard height: 30 in
- NTEP Certified 05-018
- Standard deck: 3/8 in thick diamond safety treadplate
- Standard widths from 10 ft to 14 ft
- Capacities to 400,000 lb

Options

- Side pipe rails
- Steel bulkheads
- Conversion s-beam load cell(s)
- Load cell mounting hardware
- Indicator
- Printer
- Other peripheral equipment

Specifications

Full Scale Capacity:

Standard 60,000 to 200,000 lb
Custom up to 400,000 lb

Concentrated Load Capacity (CLC):

Standard 50,000 to 70,000 lb
Custom up to 100,000 lb

Approvals:

NTEP Certified 05-018 per H-44, Class IIII
Measurement Canada AM-5598

Warranty:

One-year warranty on pivots, bearings, suspension, and mounting parts of the corner assemblies
Two-year warranty on weighbridge