



Picture is a representation of actual product

Approvals




Order Information

Load Rating	Part #	Est. Weight	Price
250 lb	17077	2 lb	Consult
500 lb	17078	3 lb	Consult
750 lb	17079	3 lb	Consult
1,000 lb	17080	3 lb	Consult
1,500 lb	17081	3 lb	Consult
2,000 lb	17082	3 lb	Consult
2,500 lb	17083	3 lb	Consult
3,000 lb	17084	3 lb	Consult
5,000 lb	17085	4 lb	Consult
10,000 lb	17086	5 lb	Consult
15,000 lb	17087	8 lb	Consult
20,000 lb	17088	16 lb	Consult

Dimensions

Rated Capacity	A	B	C	D	E
lb/in					
250	3/8-24 UNF	0.75	0.50	2.00	3.00
500 to 1,500	1/2-20 UNF	1.00	0.75	2.00	3.00
2,000 to 3,000	1/2-20 UNF	1.25	1.00	2.00	3.00
5,000	3/4-16 UNF	1.25	1.00	3.00	4.25
10,000	3/4-16 UNF	1.25	1.00	3.50	4.75
15,000	1-14 UNS	1.50	1.25	4.00	5.50
20,000	1 1/4-12 UNF	2.00	1.94	5.00	7.00



Interchangeable Products

VPG® CELTRON

STC SS..... page 189

Weigh Module Available

RICE LAKE WEIGHING SYSTEMS

**ITCM Isolated Tension
Cell Mount**..... page 28

Specifications

Full Scale Output:

3.0 mV/V

Output Resistance:

349 to 355 ohm

Input Resistance:

343 to 450 ohm

Material/Finish:

Stainless steel

Temperature:

Operating range
0 °F to 150 °F (-18 °C to 65 °C)

Seal Type:

Environmentally sealed, IP67

Safe Overload:

150% full scale

Rated Excitation:

5 to 10 V DC (15 V maximum)

Nonlinearity:

0.03% full scale

Hysteresis:

0.02% full scale

Insulation Resistance:

5,000 megohm

Cable Length:

20 ft

Cable Diameter:

0.200 in
Polyurethane jacket

Cable Color Code:

Red +Excitation
Black -Excitation
Green +Signal
White -Signal

Warranty:

One-year limited

Approvals:

cFMus